POWER HOUSE®

Lighting Controllers & Lighting Control Desk

Celebrate Occasions

Moving lights - Rhythm with your mood Create the atmosphere of celebration

- 300 W TO 5000 W PER CHANNEL
- SINGLE PHASE & THREE PHASE MODELS
- FOR LIGHTING & FOUNTAINS CONTROLS

SERIES RLH: Control lights in sequential mode. Lights are 'ON' in a sequence giving running effect. Since only one light channel is 'ON' at any given time, it also saves electrical consumption.

SERIES RLH-R: Incorporates all the features of series RLH and is provided with selection switch for forward / reverse operation.

SERIES RDL: Controls the lights with music. Music signal is connected to controller and intensity of lights is directly related with the music. Individual knobs are provided for setting of each channel at the front panel. RDL with 4th channel is for switching normal lights when the music system stops to avoid total darkness.

SERIES RMC: Control the lights with music. Audio signal is processed with 6 channel Spectrums Analyzers circuit and lights are related to specific frequency band. This is Professional grade controller and is fully automatic.

SERIES RAS: Micro controller based controller has pre-programmed 24 actions & auto light dimmer program. This is 6 channel controller. Selector switches are provided to select between action and auto dimmer mode and in action mode auto changing or fixed action to be replayed. Available for single phase and three phase input conhection.

Series RDM: professional grade dimmers with slide knob from 1 channel to 4 channel. These are manually controlled dimmers. 6 Channel dimmers a matter controller and action switch which can controls the lights in different modes.



Series PSLC: Professional grade stage light controller with 8 Channel Slide dimmers, touch pads, Music control option, and manual control for 8 Channel direct switches. Available for single phase and three phases input connections.

Series RFC: Professionals grade Musical fountain controller. Audio signal is processed with 6 channel Spectrums Analyzers circuit. Output is divided in two group. One for Lights with triak out put and other with Electro-mechinical relay for operating solenoid valves. 6 channels of lights and 6 channels for solenoid can be connected. One extra chanal for Drain Valve is provided. Since the pump in fountain system remains on even if there is no audio signal and hence all valves are off, it operates and drain out the water to keep pressure level in safe level.

SERIES RPL: It is a very compact chaser suitable for direct 3 pin plug connection, economical and attractive - it is sequential switching.



To celebrate any occasion

to move in

rhythm with

your mood

display your

heart beats, create the

atmosphere of

you need lights





ORDERING GUIDE:

- 1. Select no. of channels your lighting arrangement is.
- 2. Select the basic mode of control.
- 3. Calculate total load in each channel provide approx. 20% extra capacity for load variation due to mains fluctuations, leakage & actual consumption of load Vs claims by light makes etc.

OUR MODEL NO:

Initial 3 letters denotes the basic mode you have selected i.e. RLH for sequence runs, RDL for music controller etc.

Next 2 digits are for load i.e. 1000W is denoted by 10, or 2500W by 25.

The 3rd digit is for number of channels i.e. for 3 channel - 3, 4 channel - 4.

Sereis	FUNCTION / ACTION	No. of	Load per Channel		
		Channels	1000 W	2500 W	5000 W
RLH	Sequential switching of lights. (Unidirection)	3	RLH 103	RLH 253	RLH 503
		4	RLH 104	RLH 254	RLH 504
		6	RLH 106	RLH 256	RLH 506
RLH-R	Sequential switching of lights.	4	RLH 104R	RLH 254R	RLH 504R
	(FORWARD/ REVERSE)	6	RLH 106R	RLH 256R	RLH 506R
RDL	Light intincity controlled with music	3	RDL 103	RDL 253	RDL 503
	signal- manual settign 4th channel- no				
	out put when music is on. Full glow on	4	RDL 104	RDL 254	RDL 504
	music off				
RMC	Light are controlled with Music signal -	6	RMC 106	RMC 256	RMC 506
	automatc- spectrum analizer				
RAS	Programmed 24 actions & auto dimming with selector switch	6	RAS 106	RAS 256	RAS 506
PDM	WILLI SCIECTOL SWITCH		2500 W	6000 Watt Per Ch.	
		1	PDM 251	PDM 601	
	Electronics Dimmer with slide knob for	2	PDM 252	PDM 602 PDM 603 PDM 604	
	stage light control Electronics Dimmer	3	PDM 253		
	with slide knob & Multi action	4	PDM 254		
	sequencer- Mode selection by switch		1 Ph. Input	t 3 Ph. input option 6000 W	
		6	2500 W		
			PDM 256	PDMT 606	
PSLC	Profissional grade stage light controller		1 Ph. Input	3 Ph. input option	
	with Slide dimmers, toch pads, Music	8	2500 W	5000 W	
	control, multi acton - independent	+	PSLC 2588 PSLCT 5088		
	Manual channels	8		PSLC 2588 PSLCT 5088	
RFC	Professional grade Musical fountain	6	Lights 2500 W Per Chanel Relay out put for solonide		
	controlelr with - Spectrum Analizer	+ 6			
	separate Output for lights and solonide	+1	Relay Output for Drainout		
	provision for Drain out solonide		RFC2513		
RPL	Sequential switching of lights. Compact	3	RPL 33	300 W per channel	
	chaser suitable for direct plugin	4	RPL 34	load .	



POWER SERVICES

INNOVATIVE POWER SOLUTIONS

33, Phears Lane, Kolkata -700 073, West Bengal, India Ph. +91 (033) 2237-0508, 22360575 Fax : +91 (033) 25210322 Email: info@indiapowerhouse.net, Web: www.indiapowerhouse.com